



Infeed Test System

Typ I-TS-3870 & Typ MI-TS-3871

I-TS-3870: Single-channel system

MI-TS-3871: Multi-channel system



NEW

up to
1200 V / 1200 A

75
Jahre
Gustav Klein

NOW AVAILABLE:

The proven test system with up to 1200 V & 1200 A



Outstanding properties and a wide range of design variants:

- Various input voltages
- Highest safety standards
- Simple integration through various interfaces
- Many other options available
e.g. insulation monitoring, battery simulator / battery tester switchable and much more

Single-channel system I-TS 3870

| Model | Voltage | Power | Performance |
|-------------------------|-------------|----------|-------------|
| I-TS-3870-1200-320-600 | 10 – 1200 V | ± 600 A | ± 320 kW |
| I-TS-3870-1200-320-1200 | 10 – 1200 V | ± 1200 A | ± 320 kW |
| I-TS-3870-1200-650-1200 | 10 – 1200 V | ± 1200 A | ± 650 kW |

Two-channel system MI-TS 3871

| Model | Voltage | Power | Performance |
|----------------------------|-------------|----------|-------------|
| MI-TS-3871-1200-320-600-2 | 10 – 1200 V | ± 600 A | ± 320 kW |
| MI-TS-3871-1200-320-1200-2 | 10 – 1200 V | ± 1200 A | ± 320 kW |
| MI-TS-3871-1200-650-600-2 | 10 – 1200 V | ± 600 A | ± 650 kW |
| MI-TS-3871-1200-650-1200-2 | 10 – 1200 V | ± 1200 A | ± 650 kW |

Four-channel system MI-TS 3871

On request

For your application



Battery test



Battery emulation



Fuel cell test