



Infeed Test System

Typ I-TS-3870 & Typ MI-TS-3871

I-TS-3870: Single-channel system
MI-TS-3871: Multi-channel system

NEW
up to
1200 V / 1200 A



NOW AVAILABLE:

The proven test system with up to 1200 V & 1200 A



Outstanding properties and a wide range of design variants:

- Various input voltages
- Highest safety standards
- Simple integration through various interfaces
- Many other options available
e.g. insulation monitoring, battery simulator / battery tester switchable and much more

Single-channel system I-TS 3870

Model	Voltage	Power	Performance
I-TS-3870-1200-320-600	10 – 1200 V	± 600 A	± 320 kW
I-TS-3870-1200-320-1200	10 – 1200 V	± 1200 A	± 320 kW
I-TS-3870-1200-650-1200	10 – 1200 V	± 1200 A	± 650 kW

Two-channel system MI-TS 3871

Model	Voltage	Power	Performance
MI-TS-3871-1200-320-600-2	10 – 1200 V	± 600 A	± 320 kW
MI-TS-3871-1200-320-1200-2	10 – 1200 V	± 1200 A	± 320 kW
MI-TS-3871-1200-650-600-2	10 – 1200 V	± 600 A	± 650 kW
MI-TS-3871-1200-650-1200-2	10 – 1200 V	± 1200 A	± 650 kW

Four-channel system MI-TS 3871

On request

For your application



Battery test



Battery emulation



Fuel cell test



Caltest Instruments GmbH

Binzigstrasse 21 | Tel: +49(0)7842-99722-00
D-77876 KAPPELRODECK | Fax: +49(0)7842-99722-29
www.caltest.de | sales@caltest.de