

EL+ vHiL ePlus

Regenerative AC/DC Electronic Load




The EL+ vHiL is CINERGIA's Current Source optimized in performance and price for Power Hardware in the Loop applications. This version keeps the software and functionalities of CINERGIA's EL+ vAC and it includes Power Amplifier functions to interface with Real Time Control Systems.



Regenerative Technology

Thanks to our bi-directional topology, the AC/DC Electronic Load Converter are regenerative, resulting in a reduction of both the consumed energy during the tests and the power required from the electrical installation.

This technology allows us to work in both directions, as power generators or offering a consumption for the realization of all types of tests.




Main Applications



Electromobility




Smart Grids




Avionics



IEC Testing



Photovoltaic



Power HiL

Bidirectional and Regenerative

Clean grid current

THDi <3% and PF > 0.98


13 Models

from 7.5kW to 160kW

Parallelization of units to increase the power

Independent phase configuration of

rms current, phase angle, harmonics, interharmonics, generation of fast transients ("Current Dips")




Emulation of grid connected devices

Loads absorbing energy from grid
Generators injecting energy to the grid
Programmable Active/Reactive consumption
Non-linear currents up to CF of 3

Intuitive User Interface

Modbus/Ethernet Open protocol, Labview drivers


Bidirectional and Regenerative Hardware



The hardware platform is based on a Back-to-Back power conversion topology, formed by two IGBT-based power stages. The grid side stage is an Active Rectifier which produces clean sinusoidal currents with very low harmonic distortion and power factor close to one.

The EUT side stage can be configured for AC voltage source or AC current source or DC output. In AC, voltage/current are controlled by using state of the art digital Proportional-Resonant controllers. In DC, the three independent buck-boost bidirectional legs enable the separated control of three different DC voltages or currents.

Block Diagram



Local Interface

Analogue and Digital 10 ports

The isolated digital and analogue inputs/outputs permit the connection of the unit to External Controllers and Power Hardware in the Loop systems (option).

4.3" Touchscreen

Allows the local parameterization and command of the device, configuration of the communications link, plots the main signals and enables the local datalogging.

Safety First

The units integrate a local Emergency Stop pushbutton and two signals (input+ output) to be connected to the laboratory interlock system. Additionally, the digital outputs can be interfaced to safety tower lights.

Master/Slave

ePLUS is a modular platform enabling the master/slave connection of units with equal power.



Better than ever, the enhanced **Plus** family



What's better

MASTER/SLAVE CONNECTION

by using a fiber optics link to increase power/voltage capabilities:

GE in AC: can be connected in parallel

EL in AC: can be connected in parallel

B2C: can be connected in parallel, or series or both

FASTER

30kHz control loop frequency

MORE HARMONICS

50 per phase with 20 free-harmonics

DELTA LOAD

for the EL in AC mode

ADJUSTABLE DC TRANSIENT

controllers to improve stability of the system


OPTIMIZED RMS CALCULATION

for PV inverters anti-islanding test

SAME ELECTRICAL RATINGS

and SAME BANDWIDTH


because the power platform does not change so robustness and ratings remain the same.



Software



The user interface used by CINERGIA devices has been developed by our R&D team, to offer total control of the device, with a comfortable and intuitive design. This allows us to take full advantage of the capabilities of the device, as well as the programming and execution of standardized or self-created tests.



EL Modes




AC Operation

From this panel, the user can set all AC parameters. Each phase can be independently configured: RMS current magnitude, phase delay, harmonics content, free-frequency harmonic and transition ramps. A plot shows the expected real-time waveform, the FFT representation and the numeric data: RMS, peak, CF and THD.




Harmonics

The device can control simultaneously the magnitude of the first 15 harmonics and one free harmonic per phase. The free one allows the generation of sub-harmonics, inter-harmonics and high frequency harmonics up to the 50th, setting both the magnitude and phase delay.



Power and Impedance Control

In Power mode, the active and reactive power of each phase is independently controlled. In Impedance mode, the device emulates an RLC load allowing to parameterize resistance, inductance and capacitance per phase making this device suitable for Anti-Islanding test of grid converters.




AC




Steps Mode

One of the most remarkable novelties of the new software is the steps functionality. Step test files are saved and executed by the DSP allowing deterministic timing with a resolution of 66µs. The user gains access to all registers of the device to create complex test sequences which run directly in the converter without the need of an external computer.



Disturbance Generation

The steps mode includes predefined easy-to-use test panels. The AC faults panel is a powerful yet intuitive editor which allows generating and configuring flicker. Specific profiles can be saved in .csv files, modified, and reused by importing an existing one.



Linear & Non-Linear Emulation

The capacity to emulate linear and non-linear loads in one of the main features of the 4Q Electronic Load. Through our intuitive control software, the magnitude of harmonics can be set and different types of loads can be generated.



DC




DC Operation

This panel allows the user to access all DC setpoints and limits. Thanks to the unique Multichannel feature, each phase can have a different Operation Mode: voltage, current, power, resistance and advanced DC applications. Transition ramps, voltage and current limits can be modified. The limits for sink and source operation are different for safer testing, specially in battery applications.



Sequence

The User Interface Software integrates a Sequence Editor to create automatic test sequences, save them for future use and import them in .csv files. A smart datalogger can be activated from the LCD of the unit to record automatically the resulting voltage and current measurements with a time resolution of 400 ms.



Multichannel

Enabling the Separated Channel Control converts the device in three functionally independent DC Bidirectional Power Supplies, sharing the common negative rail. Each channel can have a different status (ON, OFF, Warning, Alarm), Operation Mode (see Range and Specifications table), Setpoint, Ramp and Limits.



Battery Pack Tester

This functionality enables the user to precisely control the charge, discharge and cycling of a Battery. Basic parameters include the charge/discharge current, fast charge and floating voltages while Advanced parameters add Energy (Ah) and Time as transition conditions. Profiles for each Battery technology can be saved and imported in .CSV files.



Battery Emulation

The B2C+ integrates a mathematical model to emulate the voltage behaviour of a real battery pack. The output voltage will change as a function of the SOC and Current. By configuring the provided parameters, the voltage profile can be adjusted to match different technologies: Lilon, NiMH, NiCd, Pb, Flux, etc.



PV Panel Emulation

The PV Panel model is based on the single-diode equivalent circuit of a PV cell and the series-parallel connection of cells to form a panel. A Runtime functionality allows the simulation of a complete day by launching different irradiance and temperature setpoints from a .csv file, enabling the user burn-in and functional tests of PV Inverters.



EL+ vAC/DC Range & Specifications

Input side (GRID side)

AC Voltage

Rated: 3x400Vrms +Neutral+ Earth

Range: +15% / -20%

Rated AC Current

Depends on model (see Wiring Manual)

Frequency

48-62Hz

Current Harmonic Distortion

THDi < 3% at rated power

Current Power Factor

PF > 0.98 at rated power

Efficiency

≥ 89% (7.5 & 10), ≥ 91% (15 to 30), ≥ 92% (40 to 200)

Output side in DC (EUT side)

Terminals

Number: 4 (3 phases + 1 neutral)

Configuration of Channels

Unipolar 3-channels 2Q, independent setpoints per channel

Unipolar 1-channel 2Q, one global setpoint for all channels

Multichannel: 2Q, independent start/stop, operation mode and setpoints per channel (note: multichannel is an option for ≥ 80kVA)

Bipolar (4Q two independent setpoints)

Voltage (CV)

Range: 2Q: 20⁽¹⁾ to 750V (800V with High Voltage option)

4Q: 0 to +350V / 0 to -350 (+ rail / 0 / - rail, Bipolar configuration)

Setpoint Resolution: 10mV

Effective Resolution⁽²⁾: < 0.05% of FS⁽³⁾

Setpoint Accuracy⁽⁴⁾: ± 0.1% of FS⁽³⁾

Transient Time⁽⁵⁾: < 1ms (10% to 90% at a step to V_{rated})

Ripple⁽⁷⁾ (peak-peak): < 0.55% of FS⁽³⁾

Current Mode (CC)

Range: from 0 to ± 110% of I_{rated} (see models table)

Setpoint Resolution: 10mA

Effective Resolution⁽²⁾: < 0.05% of FS⁽³⁾ (< 0.1% models 7.5 & 10)

Setpoint Accuracy⁽⁴⁾: ± 0.2% of FS⁽³⁾

Transient Time⁽⁵⁾: < 1ms (10% to 90% at a step to I_{rated})

Ripple⁽⁷⁾ (peak-peak): < 0.7% of FS⁽³⁾

Power Mode (CP)

Range: from 0 to ± 200%⁽⁸⁾ of P_{rated} (see models table)

Derived current setpoint: P_{setpoint} / V_{measured}

Setpoint Resolution: 1W

Effective Resolution⁽²⁾: < 0.1% of FS⁽³⁾ (< 0.25% models 7.5 & 10)

Setpoint Accuracy⁽⁴⁾: ± 0.4% of FS⁽³⁾

Transient Time⁽⁵⁾: < 2.5ms (10% to 90% at a step to P_{rated})

Resistance Mode (CR)

Range: from 0.1 to 1000 Ohm

Derived current: V_{measured} / R_{setpoint}

Setpoint Resolution: 0.01 Ohm

Setpoint Accuracy⁽⁴⁾: ± 0.2% of FS⁽³⁾

Transient Time⁽⁵⁾: < 2ms (10% to 90% at a step to R_{rated})

Output side in AC (EUT side)

Terminals

Number: 4 (3 phases + 1 neutral)

Configuration of Channels

3 channels: 4Q, independent setpoints per phase

1 channel: 4Q, global setpoints for all phases (only in GE+)

Multichannel: 4Q, independent start/stop, alarm status and setpoints per phase (note: multichannel is an option for ≥ 80kVA)

Output side in EL-AC

Admissible Voltage

Connection: 1-phase, 3-phase star or 3-phase delta

Maximum: $\pm 400\text{V}$ peak

Range: 10-100Hz

35⁽¹⁾ to 277Vrms phase-neutral (295Vrms with HV option)

35⁽¹⁾ to 480Vrms phase-phase (510Vrms with HV option)

>100Hz: maximum rms voltage follows $V \cdot f < 46000$

Frequency: 10 to 400Hz

Current Mode (CC)

Range: from 0 to $\pm 200\%$ ⁽⁸⁾ of I_{rated} (see models table)

Setpoint Resolution: 10mA_{rms}

Effective Resolution⁽²⁾: $< 0.05\%$ of $FS^{(3)}$ ($< 0.1\%$ models 7.5 & 10)

Setpoint Accuracy⁽⁴⁾: $\pm 0.2\%$ of $FS^{(3)}$

Transient Time⁽⁵⁾: $< 1.5\text{ms}$ (10% to 90% at a step transient)

Ripple⁽⁷⁾ (peak-peak): $< 0.7\%$ of $FS^{(3)}$ (with Low Ripple Inductor option)

Phase Angle (cos ϕ)

Range: -90 to 90° in Sink / Source

Resolution: 0.01°

Enhanced

Harmonics

Range: up to 50th

50 independent harmonics per phase:

20 free programmable frequency and phase from 0.1 to 50 times f_0

30 fixed frequency

Harmonics content: $V \cdot f < 46000$ (with current derating)

Setpoint Accuracy⁽⁴⁾: same as current accuracy

Small Signal Bandwidth: up to 5000Hz ⁽⁹⁾

Transient Time⁽⁵⁾: $< 2\text{ms}$ (10% to 90% at a step change)

Power Mode (CP / CS)

Range: from 0 to $\pm 200\%$ ⁽⁸⁾ of P_{rated} (see models table)

Derived current setpoint: calculated from ISI and $\Phi(S)$

Setpoint Resolution: 1W, 1VA

Effective Resolution⁽²⁾: $< 0.1\%$ of $FS^{(3)}$ ($< 0.25\%$ models 7.5 & 10)

Setpoint Accuracy⁽⁴⁾: $\pm 0.4\%$ of $FS^{(3)}$

Transient Time⁽⁵⁾: $< 2.5\text{ms}$ (10% to 90% at a step to P_{rated})

Enhanced

Impedance Mode (CZ)

Calculation method configurable (rms, instantaneous)

Range: from 0.8 to 1000 Ohm , 0.1 to 2000mH , 0 to 3.7mF

Derived current/phase setpoint: calculated from IZI and $\Phi(Z)$

Setpoint Resolution: 0.01 Ohm/mH/mF

Setpoint Accuracy⁽⁴⁾: see current accuracy

Transient Time⁽⁵⁾: $< 2.5\text{ms}$ (10% to 90% at a step to R_{rated})

Operation Modes

DC

Programmable Current (CC)

Power Amplifier (HiL)

Steps

Optional Programmable Voltage (CV)

Optional Programmable Power (CP)

Optional Programmable Resistance (CR)

Optional Battery Testing (BTest) (charge/discharge/cycling)

Optional Battery Emulation (BEmu)

Optional PV Panel Emulation (PVEmu)

AC

Programmable Current (CC)

Power Amplifier (HiL)

Steps

Optional Programmable Power (CP / CS)

Optional Programmable Impedance (CZ)

Overload/ Overcurrent

Admissible DC overcurrent is: 110% of rated value during 1 minute

Admissible AC overcurrent: 125% of rated value during 10 minutes,
150% during 1 minute, 200% during 2 seconds

Admissible overloads: 125% of rated value during 10 minutes,
150% during 1 minute, 200% during 2 seconds

User Interface

Local Control (4.3" Touchscreen panel)

Isolated Digital port: 6 inputs, 4 outputs

Isolated Analogue port: 6 inputs (rms setpoints or power amplifier), 6 outputs (rms readback or real-time readback)

Interlock port: 1 NC Input, 1 NO Output

Emergency Stop pushbutton

Remote Control Port

LAN Ethernet with Open Modbus-TCP protocol

RS485 (option), CAN and RS232 (using external gateway)


Software

Graphical User Interface for Windows 7/10

LabView drivers and open Labview interface example

Emergency Stop
pushbutton

Touchscreen panel



Enhanced


Master/Slave Operation

Connection: fiber optics link (x6)

Configuration: from software user interface/MODBUS up to 8 units:

AC: Parallel

DC: Parallel, serial or serial-parallel



Size and Weight

Models 7.5 to 60 kW

Height

1100 mm

Width


450 mm

Depth

770 mm

Weight

200 kg



Models 80 to 120 kW

Height

1320 mm

Width

875 mm

Depth

870 mm


Weight

400 kg




Models 160 & 200 kW

- Height
2000 mm
- Width
900 mm
- Depth
850 mm
- Weight
680 kg




Connections



The distribution of the connectors may change depending on the models

Selectors



The type of selectors and their location may change depending on the models

Protections

Overvoltage (peak, rms), Overcurrent (peak, rms), Overload
Shortcircuit, Emergency Stop, Watchdog, Heart Beat, Output
Contactar, Wrong Configuration
Alarms and Limits are user configurable and can be saved in a
password protected EEPROM

Mesurements ⁽⁶⁾

Grid Voltage (rms), Current (rms), Power (P,O) and Frequency
Output Voltage (rms, avg), Current (rms, avg), Power (P,O) and Frequency
Heatsink Temperatures (x2) and DC Link Voltage
Datalogging available through FTP connection

Ambient

Operating temperature⁽⁸⁾ : 5–40°C
Relative Humidity: up to 95%, non-condensing
Cooling: Forced air
Acoustic noise at 1m: < 52dB(A)(7.5 to 60), < 65dB(A)(80 to 120), < 70dB(A)(160 and 200)

Standards

CE Marking
Operation and Safety: EN-50178, EN-62040-1
EMC: EN-62040-2
RoHS

All specifications are subject to change without notice.

Options

Choose your options:

- Three channel mode: allows different operation mode start/stop/reset per channel (included in all models from 7.5 to 60, both included)
- 30kHz Switching Frequency: only available far models 15 (derated to 7.5kW), 20 (derated to 7.5kW) and 30 (derated to 10kW)
- Isolation monitor (advised far IT systems)
- Low current ripple inductance (included in all models ≤54kW. optional far models ≥80kW)
- High Frequency 360 - 900 Hz
- Anti-islanding monitor (only advised in net injection to the grid and following local regulations)
- High Voltage (HV): voltage up to 295Vrms phase-neutral in AC up to 800V in DC
- RS485
- Battery Emulation
- Battery Test
- PV Panel Emulation
- CV, CP, CR, CZ and CP/CS

All specifications are subject to change without notice.

1. Minimum voltage setpoint is 0V in DC. The recommended minimum setpoint far long-term use is 20Vrms in AC and 20V in DC,
2. Effective resolution measured with a 400ms window
3. FS Range of voltage is 800V (with High Voltage option)
FS Range of current is 2·13 · I rated I (see models table)
FS Range of power is 2·1200% · Prated I (see models table)
4. Accuracies are valid far settings above 10% of FS
5. Measured with the rated resistive load and high-dynamics controllers configuration.
6. Accuracy of measurements is ±0.1% of FS far rms voltage, ±0.2% of FS far rms current, ±0.4% of FS far active power (valid only above 10% of FS)
7. Consult us far lower voltage/current ripple requirements
8. Rated power figures are given at 20 °C
9. The maximum output voltage depends on frequency following $V \cdot f < 46000$

Models

EL+ vHiL

Reference	AC Power Rated ⁽⁹⁾	AC Current Rated ⁽⁹⁾ RMS 3 channels / 1 channel	DC Power Rated ⁽⁹⁾	DC Current Rated ⁽⁹⁾ RMS 3 channels / 1 channel	Weight (kg)	Dimensions DxWxH (mm)
EL+7.5 vHiL	7.5 kW	11 A / 33 A	3.75 kW	±5 A / ±15 A	155 kg	770 x 450 x 1100 mm
EL+10 vHiL	10 kW	15 A / 45 A	5 kW	±7.5 A / ±22.5 A	155 kg	770 x 450 x 1100 mm
EL+15 vHiL	15 kW	22 A / 66 A	7.5 kW	±10 A / ±30 A	155 kg	770 x 450 x 1100 mm
EL+20 vHiL	20 kW	29 A / 87 A	10 kW	±12.5 A / ±37.5 A	155 kg	770 x 450 x 1100 mm
EL+30 vHiL	27 kW	40 A / 120 A	13.5 kW	±15 A / ±45 A	155 kg	770 x 450 x 1100 mm
EL+40 vHiL	40 kW	58 A / 174 A	20 kW	±20 A / ±60 A	200 kg	770 x 450 x 1100 mm
EL+50 vHiL	50 kW	73 A / 219 A	25 kW	±25 A / ±75 A	200 kg	770 x 450 x 1100 mm
EL+60 vHiL	54 kW	80 A / 240 A	27 kW	±28.5 A / ±85.5 A	200 kg	770 x 450 x 1100 mm
EL+80 vHiL	80 kW	116 A / -	40 kW	±52.5 A / ±157.5 A	400 kg	870 x 875 x 1320 mm
EL+100 vHiL	100 kW	145 A / -	50 kW	±65 A / ±195 A	400 kg	870 x 875 x 1320 mm
EL+120 vHiL	108 kW	157 A / -	54 kW	±65 A / ±195 A	400 kg	870 x 875 x 1320 mm
EL+160 vHiL	145 kW	211 A / -	72.5 kW	±77.5 A / ±232.5 A	680 kg	850 x 900 x 2000 mm
EL+200 vHiL	160 kW	232 A / -	80 kW	±92.5 A / ±277.5 A	680 kg	850 x 900 x 2000 mm

All specifications are subject to change without notice.

For EL mode is not available a physical 3 channel/1 channel switch. To work in a single phase mode, it's necessary to introduce a monophasic grid at the output.

Galvanic Isolation

	Circuit Breaker Recommended	Weight
Inside the cabinet	IT 7.5i Type C - 25 A	145 kg
	IT 10i Type C - 25 A	145 kg
	IT 15i Type C - 32 A	145 kg
	IT 20i Type C - 40 A	145 kg
	IT 30i Type C - 50 A	195 kg
	IT 40i* Type C - 63 A	195 kg
	IT 50i* Type C - 83 A	195 kg

*In the IT 40i and IT 50i models the size of the cabinet increases to a total of 770 x 835 x 1100 mm. The others keep the original size.

	Circuit Breaker Recommended	Weight	Dimensions D x W x H
In external cabinet IP20	IT 30e Type D - 80 A	174 kg	595 x 415 x 708 mm
	IT 40e Type D - 100 A	217 kg	725 x 525 x 773 mm
	IT 50e Type D - 125 A	280 kg	725 x 525 x 773 mm
	IT 60e Type D - 160 A	381 kg	875 x 600 x 900 mm
	IT 80e Type D - 200 A	435 kg	875 x 600 x 900 mm
	IT 100e Type D - 250 A	458 kg	875 x 600 x 900 mm
	IT 120e Type D - 315 A	514 kg	875 x 600 x 900 mm
	IT 160e Type D - 400 A	612 kg	964 x 648 x 1252 mm
	IT 200e Type D - 500 A	753 kg	1192 x 744 x 1430 mm

Configuration Modes

EL+ AC	PHiL DC	PHiL AC	DC
--------	---------	---------	----

Master / Slave

Parallel	in AC modes (GE & EL)		
Parallel	Serial	Serial Parallel	in DC mode

Channel Configuration in EL

3 channels	* 1 channel	*For 1-channel configuration contact us.
------------	-------------	--

Channel Configuration in DC

3 channels	1 channel	Bipolar	Unipolar
------------	-----------	---------	----------

Regenerative Power Electronic Solutions



Caltest Instruments GmbH

Binzigstrasse 21 | Tel: +49(0)7842-99722-00
D-77876 KAPPELRODECK | Fax: +49(0)7842-99722-29
www.caltest.de | info@caltest.de



Can Baletes 7, Nau A
08310 Argentona
Barcelona (Spain)
+34 934 864 358
cinergia@cinerגיapower.com

Follow us on:
Youtube, LinkedIn, Twitter